



Data Sheet

MiniLine ML100.105 with DC 48-56V / 100W

- Mounted and connected within seconds, no tools required
- World-wide approvals (UL, EN, CSA, CB Scheme) for industry and office/home
- Tiny: WxHxD = 73 x 75 x 103mm
- Adjustable output voltage up to DC 56V
- 115/230V Auto Select Input
- PULS Overload Design (high output overload capability)
- Selectable single/parallel operation (jumper)

◆ Technical Data ML100.105

◆ Input

| | |
|-------------------------------------|--|
| Input voltage | AC 100-120/220-240V (Auto Select), 50...60 Hz (AC 85...132V / AC 184...264V, DC 220...375V, N=⊕ and L=⊖) |
| Input current | <2.1A (@ AC 100V _{in} , 100W P _{out}) <1A (@ AC 220V _{in} , 100W P _{out}) |
| External fusing | not required, unit provides internal fuse (T3A15H, not accessible) |
| Transient immunity | Transient resistance acc. to VDE 0160 / W2 (750V/ 1.3 ms), over entire load range |
| Hold-up time (see diagram below) | >40 ms @ AC 230V, 48V / 2.1A >20 ms @ AC 196V, 48V / 2.1A >20 ms @ AC 100V, 48V / 2.1A |

◆ Efficiency, Reliability

| | |
|--------------------|--|
| Efficiency | typ. 91% (AC 230V, 48V / 2.1A) (see also diagram below) |
| Losses | typ. 10W (AC 230V, 48V / 2.1A) |
| MTBF (Reliability) | appr. 500.000 h acc. to Siemensnorm SN 29500 48V / 2.1A, AC 230V, T _{amb} = +40 °C |

Prior to shipment, every unit undergoes the following tests in order to isolate any defective units which might suffer an early failure:

- Run-in/burn-in (Full load, T_{amb} = +60°C, on/off cycle)
- Functional test (100 %)

◆ Construction, Mechanics, Installation

Robust plastic housing (US Patent No. D442, 9235), fine ventilation grid on three housing sides to keep out small parts (e.g. screws), IP20

Dimensions and weight

- W x H x D 73 mm x 75 mm x 103 mm (+ DIN rail)
Depth incl. terminals: 98 mm (+ DIN rail)
- Weight 360 g

Mounting orientation  (cf. 'Output')

Ventilation/Cooling Normal convection, no fan required

- Free space f. cooling recom'd.: 25mm on sides with ventilation grid

Easy snap-on mounting onto the DIN-rail (TS35/7,5 or TS35/15).

Unit sits safely and firmly on the rail; no tools required even to remove

Connection by Spring Clamp terminals; uniformly firm hold, vibration-resistant and maintenance-free: 2 terminals per output

Connector size range

- flexible cable 0.3-2.5mm² (28-12 AWG)
- solid cable 0.3-4mm² (28-12 AWG)
Ferrules admissible
- Wire strip length 6mm recommended

◆ Output

| | |
|--------------------------|---|
| Output voltage | DC 48-56V (adj. by front panel potentiometer) • preset 48V ± 0.5% @ 2.1A |
| Voltage regulation | stat. <1% V _{out} (Jumper in pos. 'Single Use') stat. <3% V _{out} (Jumper in pos. 'Parallel Use'), dyn. ±1.5% V _{out} over all |
| Ripple/Noise | <50mV _{pp} (20 MHz bandw., 50 Ω measur.) |
| Overvoltage prot. (OVP) | <60V |
| Rated continuous loading | up to 2.1A @ 48V / 1.8A @ 56V (convection cooling), depending on built-in orientation, V _{in} and T _{amb} For details see derating diagram below |
| Overload behaviour | PULS Overload Design: No switch-off at overload/short-circuit, instead: up to 1.9 · I _{rated} . So you need no oversizing to start awkward loads. |
| Protection | Unit is protected against (also permanent) short-circuit, overload and open-circuit. |
| Derating | depending on built-in orientation; see diagram below |
| Parallel operation | yes (selectable by front panel jumper) |
| Power back immunity | 63V |
| Operating indicator | Green LED |

◆ Environmental Data, EMC, Safety

Ambient temperature range (measured 25 mm below unit)

- storage/transport -25°C ... +85°C
- operation -10°C ... +70°C (for derating see diagram below)

Humidity max. 95% (without condensation)

Safe low voltage: SELV (IEC/UL 60950-1, VDE0100/T.410), PELV (EN 50178)
Prot. class/degree: Class 1 (IEC/UL 60950-1) / IP20 (EN 60529)

This unit fulfills all major **safety approvals**

UL 508 LISTED: E198865,
IEC 61010-2-201 Manufacturer's Declaration,
IEC 60950-1 CB Scheme,
UL 60950-1: E137006 US and Canada,
Marine DNV: TAA00002JT


CE: EU Declaration of Conformity (EU DoC): 2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU (RoHS),
WEEE Directive (2012/19/EU), WEEE-Reg.-Nr. DE 55837529

Design details – for your advantage:


- All terminals are easy to reach as mounted on the front panel.
- Input and output are strictly apart from each other (input below, output above) and so cannot be mixed up.
- **Mounting and connection do not require any screwdriver**
→ Easy, quick, durable and reliable installation.

◆ Diagrams


Output characteristic V_{out}/I_{out} (min.)



Efficiency (@ V_{out} = 48V, typ.)



Derating of output power



Hold-up time with ACin (at V_{out} = 48V, typ. + min.)

