

Ref. Certif. No.

DK-111289-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Trademark (if any)

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

Protection module with integrated electronic fuses

PULS GMBH **ELEKTRASTR 6 MUNCHEN 81925** GERMANY

PULS GMBH **ELEKTRASTR 6 MUNCHEN 81925** GERMANY

See Page 3 Additional Information on page 2

See Page 2 Additional Information on page 2



PISA-B-812-B1, PISA-B-812-B4, PISA-B-8CL2-B1, PISA-B-8CL2-B4 PISA-B-812-B1-70, PISA-B-8CL2-B1-72, PISA-B-810.000. Additional Information on page 2

Additionally evaluated to EN 61010-1:2010/A1:2019; EN IEC 61010-2-201:2018. National Differences specified in the CB Test Report.

Additional Information on page 2

IEC 61010-1:2010, IEC 61010-1:2010/AMD1:2016, IEC 61010-2-201:2017

E198865-4789663277-CB issued on 2021-03-18

This CB Test Certificate is issued by the National Certification Body



□ UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
⊠ UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
□ UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
□ UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2021-03-26

Signature:

Jan-Erik Storgaard



Ref. Certif. No.

DK-111289-UL

Model and Ratings:

Model No. PISA-B-812-B1, PISA-B-812-B4, PISA-B-812-B1-70, PISA-B-800.000 Input: DC 24, 40A Output: Channel 1-2: DC 24V, 1-12A adjustable Channel 3-8: DC 24V, 1-10A adjustable Channel 1-2 optimized for capacitive loads Operational temp. range: -25°C to +70°C Model No. PISA-B-8CL2-B1, PISA-B-8CL2-B4, PISA-B-8CL2-B1-72 Input: DC 24, 30A (40A with extension modules) Output: Channel 1-8: DC 24V, max. 100VA Channel 1-2 optimized for capacitive loads Operational temp. range: -25°C to +70°C

Additional information (if necessary)



□ UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☑ UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
□ UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
□ UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2021-03-26

Signature: *V* Jan-Erik Storgaard

for our Superial



Ref. Certif. No.

DK-111289-UL

Factories:

PULS ELECTRONICS (SUZHOU) CO LTD NO 1 RUI EN LANE XINGPU RD, SIP SUZHOU JIANGSU 215021 CHINA

PULS INVESTICNI S R O PRAZSKA 5639 430 01 CHOMUTOV CZECH REPUBLIC

Additional information (if necessary)



□ UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☑ UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
□ UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
□ UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2021-03-26

Signature: Jan-Erik Storgaard